



CK24 W
180 amp @ 100% Duty Cycle

CK Worldwide offers a complete line of industry standard torch models.

Standard features include:

Brass instead of copper head (eliminate seizing, stripping or galling of threads)

Fail-Safe hose fittings (no wire ties required)

Silicon rubber insulation provides best protection against high frequency leakage

Superflex cables on all Rapid Stock Torches

Flex Head



Water Cooled



8 SERIES

CUP	COLLET BODY	COLLET	HEATSHIELD	TORCH
CERAMIC 8C4 (53N24) 8C5 (53N25)	8C6 (53N27)	STANDARD 8CB20 (53N17) 8CB40 (53N18) 8CB116 (53N19) 8CB332 (24CB332)	STANDARD 8C20 (53N15) 8C40 (53N16) 8C116 (53N14) 8C332 (24C332)	STANDARD 80THS
ALUMINA 8A1 (A53N23) 8A4 (A53N24)	8A5 (A53N25) 8A6 (A53N27)			
CERAMIC - LONG 8C4L (53N28)	8C6L (53N26)			
ALUMINA - GAS LENS 2AG4 (53N50) 2AG5 (53N59)	2AG6 (53N60) 2AG7 (53N61)	GAS LENS 2GL20 (45V41) 2GL40 (45V42) 2GL116 (45V43) 2GL332 (45V44)	GAS LENS 8CG20 (53N62) 8CG40 (53N63) 8CG116 (53N64) 8CG332 (24GLC332)	GAS LENS 8GHS
CERAMIC 8C4 (53N24) 8C5 (53N25)	8C6 (53N27)	GAS LENS 8GL332	GAS LENS 8C332 (24C332)	GAS LENS 8GHS
ALUMINA 8A1 (A53N23) 8A4 (A53N24)	8A5 (A53N25) 8A6 (A53N27)			
CERAMIC - LONG 8C4L (53N28)	8C6L (53N26)			

**TORCHES
USED ON:**
 CK80
 CK90
 CK180
 CWH180
 CK24
 CK24W

TUNGSTEN ELECTRODE CONVERSION CHART		
Size Suffix	Inches	Millimeters
020	.020"	.5mm
040	.040"	1.0mm
116	1/16"	1.6mm
332	3/32"	2.4mm
418	1/8"	3.2mm
532	5/32"	4.0mm
316	3/16"	4.8mm
1400	1/4"	6.4mm