# **PLYMIVENT®**

clean air at work

## **WORKING LIGHT**

#### **WORKING LIGHT FOR DOWNDRAFT TABLE**

Working light, to be mounted to the back panel or backdraft panel of a downdraft table. The cable, which is provided with a protective hose, is to be connected at the rear.

The cover can be hinged to facilitate exchange of the fluorescent light. The working light is activated upon turning on the main switch of the downdraft table.



#### **SPECIFICATIONS**

■ Physical dimensions and properties		
Dimensions cover: • length • width • height	• 1325 mm (52.17 in.) • 153 mm (6.02 in.) • 111,5 mm (4.39 in.)	
Material	sheet metal	
Colour	yellow RAL 1004 (gloss grade 85%)	
Weight (net)	6,8 kg (15.0 lbs)	
Connection cable	2,3 m (7.5 ft)	
■ Electrical data		
Lamp type	fluorescent light T8	
Lamp size: • length • diameter	• 650 mm (25.6 in.) • Ø 50,8 mm (2 in.)	
Power consumption	18 W	
Connection voltage	230V/1~/50Hz	
Protection class	IP 65	
Plug type	IEC	
■ Product combination	ons	
DraftMax Eco	downdraft table to be connected to external extraction and filtration facility	
DraftMax Basic	downdraft table with disposable filter (with back panel or backdraft kit)	
DraftMax Advance	downdraft table with manual self-cleaning filter (with back panel or backdraft kit)	
DraftMax Ultra	downdraft table with automatic self-cleaning filter (with back panel or backdraft kit)	
■ Scope of supply		
Covered light fixture with fluorescent light and 2,3 m (7.5 ft) of cable and plug - Bolt M6 (6) - Tie-wrap (3)		
■ Order information		
Article number: • 230V/50Hz	• 0040300010	

• 0040300040

Number/package	1	
■ Shipping data		
Gross weight	7.8 kg (17.2 lbs)	
Packing dimensions	1330 x 155 x 170 mm (52.4 x 6.1 x 6.7 in.)	
Harmonized Tariff Code	8421.39.2090	
Country of origin	the Netherlands	

#### **APPROVALS/CERTIFICATES**

CE	
RoHS	Directive 2011/65/EC (RoHS) valid as of 8 June 2011

#### **FEATURES**

Waterproof light fixture	
Protective hose	

Product type
Article no.
Product category
Version

### Working light

refer to order information options and accessories 020312/G

Always check the latest version on **www.plymovent.com**.

• 115V/60Hz