

ProMIG-350-15-4-400V W ProMIG-500-15-4-400V W ProMIG-630-15-4-400V W

up to **3** years
warranty

INDUSTRIAL INVERTER MIG/MAG MACHINES PATON PROMIG-350/500/630 W

are designed for industrial use in MIG/MAG, MMA and TIG welding modes. The machines have a potent, high-quality metal 4-roller wire feed mechanism with a sealed motor. Also, machines are equipped with connectors for connecting an autonomous cooling unit and liquid-cooled MIG/MAG torches. In combination with high power and productivity, these machines have small weights and overall dimensions.



Processes



Input



Output



PARAMETERS

	ProMIG-350 W	ProMIG-500 W	ProMIG-630 W
Rated voltage of mains 50 / 60Hz, V	3 × 380, 3 × 400		
Rated current consumption from the mains phase, A	16,0–18,5	30,0–35,5	42,0–49,0
Rated welding current, A	350	500	630
Maximum operating current, A	450	630	800
Supply voltage variation limits, V	±15%		
Duty cycle, %	70% / 350A 100% / 290A	70% / 500A 100% / 420A	70% / 630A 100% / 520A
Limits of regulation of welding current, A	14–350	16–500	18–630
Limits of regulation of welding voltage, V	12–30	12–40	12–44
Standards	EN IEC 60974-1		
Protection class	IP33	IP23	
Insulation class	H		
Operating temperature range	–25 ... +45°C		
Welding wire diameter, mm	0,6–1,4	0,6–1,6	0,6–2,0
Welding pulse modes	MMA: 0,2–500Hz; TIG: 0,2–500Hz; MIG/MAG: 30–300Hz		
Arc striking voltage, V	110		
Rated consumption power, kVA	10,7–12,3	19,9–23,6	27,8–32,5
Maximum power consumption, kVA	15,3	29,0	40,1
Cooling	Adaptive		
Wire feeder mechanism	4 roller		
Maximum weight of the coil, kg	18		

ADVANTAGES



FRONT CONTROLS



- 1 Digital display
- 2 Welding mode selection button
- 3 The regulator for selecting the functions (parameters)
- 4 Welding program selection button
- 5 Button for testing shielding gas supply (wire is not fed)
- 6 Button for adjusting the welding voltage on the wire feeder
- 7 Digital display of the wire feeder
- 8 The regulator for selecting the functions (parameters)
- 9 Welding program selection button on a wire feeder
- 10 Wire threading button (no gas is supplied)
- 11 EURO type KZ-2 connector for connecting a semi-automatic torch
- 12 Breaker for turning on/off the welding current source
- 13 Quick coupling (blue) coolant supply
- 14 Quick coupling (red) coolant outlet
- A Bayonet-type power current socket "+"
- B Bayonet-type power current socket "-"



APPLICATIONS

A wide range of welding works at any format manufacturing and service industrial enterprises, especially those working in the fields of metallurgy, metalworking, shipbuilding, and ship repair.



COMPLETE SET



- 1 — Welding cable with ABICOR BINZEL «ground» terminal (for ProMIG-500/630-15-4-400V W)
- 2 — Welding cables with ABICOR BINZEL electrode holder and «ground» terminal (for ProMIG-350-15-4-400V W)
- 3 — Belt for carrying the device on the shoulder (for ProMIG-350-15-4-400V W)
- 4 — Fitting for quick-release gas hose connection, set of rollers for 4 diameters of steel and 2 diameters of aluminum wire

1



2



3



4



COMPATIBILITY WITH PUSH-PULL TORCHES

WITH SPECIAL ORDER



COMMUNICATION CABLES SET



MODEL	LENGTH
CCS-350-1PW	1 m
CCS-350-5PW	5 m
CCS-350-10PW	10 m
CCS-500-1PW	1 m
CCS-500-5PW	5 m
CCS-500-10PW	10 m
CCS-630-1PW	1 m
CCS-630-5PW	5 m
CCS-630-10PW	10 m