

Quick-action connection-Hose pin


Acetylene, Propane

Argon & Oxygen



Product features

- Quick-action connection according to EN561, ISO 7289.
- Safe interruption of gas flow through automatic gas shut-off when disconnecting.
- No mixing up by different coding of coupling pins.
- Prevents accidental disconnection.
- All metal components in brass 2,0401 / spring 1,4310.
- Push-system connection.






Safety elements of the GasiQ quick action connection:

- SV, Shut-off valve.

Maintenance:

- Connections are wearing parts and have to be tested by a qualified and authorised person (at least once per year)
- The tests have to be performed when the connections are connected as well as disconnected. Leakage test are to be performed with inert gas or air (free from oil and grease) or the operating gas.

Flowchart



Flow rates [air]:

pv = Primary pressure

ph = Secondary pressure

Δp = Primary pressure minus Secondary pressure


Conversion Factors:

0,1 MPa = 1 bar = 100 kpa = 14,504 psi

1 m^3/h = 35,31 cu ft/h

	A	H	P	M	M	O	E	L
QG ►	C2H2	H2	C3H8	CH4+C	CH4	O2	C2H4	C3H6
F	1,2	3,8*	0,9	1,25	1,4	0,95	1,02	0,92

Exampel:



$$QG = QD \times F$$

$$QG \blacktriangleright A = 6,4 \times 1,2 = 7,68 \text{ m}^3/\text{h C2H2}$$

QG = flow / gas type

F = conversion factor

QD = flow / air

Technical data

Gas type: Acetylene / Propane / Oxygen / Argon

Working pressure:

Acetylene 0,15MPa / 1,5 bar

Propane 2,0MPa / 20 bar


Oxygen 2,0MPa / 20 bar

Argon 2,0MPa / 20 bar

Gas temperature: -20°C up to +70°C (Oxygen -20°C up to +60°C)

Ambient temperature: -20°C up to +70°C

Dimensions



Quick-action connection F	Hose pin			
Oxygen	5mm	6,3mm	8mm	10mm
Argon	5mm	6,3mm	8mm	10mm
Acetylene / Propane		6,3mm	8mm	10mm