

Hard work never felt so easy.

(optrel



HELIX 6

reddot winner 2023 best of the best



(optrel

HELIX

PROTECTING PROFESSIONALS

The slide-up welding helmets for the very toughest working conditions.

The fully integrated slide-up welding helmet with internal glare protection and super-compact dimensions at minimal weight.

Equipped with adaptive ShadeTronic[®] technology, XXL panoramic field of vision, IsoFit[®] headband and the new optrel hardHat industrial safety helmet.

Benefit from peak performance even in the most challenging environments:

- Non-stop working without changing helmets switch between welding, grinding and cutting.
- Superior field of vision for unrestricted visibility.
- Minimum strain on the neck muscles for lasting comfort.
- Maximum comfort, without compromise.



Shade level 14* depending on mode









Slide-up function

Two visor positions: one for welding [1] and one with a clear view for grinding and other work [2] Minimiser

For an even more compact shape in the tightest of spaces

IsoFit[®] headband

For maximum customisation options

H=-17

optrel Hat

Industrial safety helmet to EN 397 standard, available in black or white





Weighs 620g

pano mode

Welding with panoramic XXL field of vision and fully automatic adjustment of protection level.



2 clear mode

Clear vision for all other work – with the visor up and full face protection. The helmet remains compact in shape.

Combined with an extremely low overall weight of approximately 620 g, it is the ideal companion for heavy-duty welding applications, even in the tightest of spaces.

No compromises. Full stop.

Thanks to our innovative slide-up technology, you can adapt to the conditions of the job within seconds.





Perfectly balanced.

The helix is perfectly balanced at all times, which – unlike conventional flip-up helmets – prevents neck and shoulder pain.

No more tunnel vision.

Keep everything in sight at work – with a field of vision six times larger than comparable products.





Effortlessly lightweight.

Full protection and maximum adaptability – and lighter than ever.

Practically made for each other: helix and the swiss air TH3 or TM3 PAPR system from optrel.

Two experts in their field. optrel helix and swiss air are high-performance athletes who work in perfect unison.

Both ultra-compact in size, super-lightweight and designed for maximum efficiency and performance.

With the optrel 'swiss air' fresh air system, you always have enough fresh air available. The respiratory support technology and the ultra-flat and lightweight rucksack design reduce the fatiguing effect, so you can complete even demanding jobs more easily.





Positive pressure principle for respiratory support



Half mask or silicone mask?

Half mask: Protection factor 500. tightfit silicone mask: Protection factor 2000. tightfit silicone mask available in sizes S, M and L.

(optrel тнз 9.8% CI FAN AIR

mountainbreeze

Spark guard

Pre-filter




ABEIP combination filter

Particle filter

Particle filter or combination filter?

Particle filter: Traps aerosols, smoke, particles and viruses.

Combination filter (gas and particle filter): Traps gases, vapours, aerosols, smoke, particles and viruses.





Particle filter

ABE1P combination filter

Respiratory protection with a cooling effect: The optrel helix pure air for connection to the optrel e3000X system.

The optrel e3000X system is the robust and reliable solution if you need TH3 or ATEX-certified respiratory protection.

The e3000X is a highly modular respiratory protection solution that you can adapt to your specific protection requirements in seconds.

In addition to the TH3 particle filter, an odour filter insert and an ABE1 gas filter are also available.

Combined with the optrel helix air, it makes the ideal system for reliable and versatile protection when working in hazardous environments.

TH3 certified optrel

ATEX-certified

99.8%

m^{ountainbreeze} Odour filter helix with the shoulder-length FaceSeal for more comfort and protection for your neck.

ABE1905 filter

TH3 particle master filter

pre-filter

Spark guard

AVAILABLE IN THREE OPTICAL VERSIONS, EACH WITH AND WITHOUT PAPR CONNECTION. TECHNICAL DATA



HELIX



HELIX



HELIX

| | QUATTRO | CLT | 2.5 |
|---|--|---|--|
| | Art. no. 1050.100 PAPR**: Art. no. 4441.940 | Art. no. 1050.200 PAPR**: Art. no. 4441.960 | Art. no. 1050.000 PAPR**: Art. no. 4441.980 |
| XXL panoramic field of view clear- view | * 180° | √ 180° | ✔ 180° |
| Weight of helix welding helmet incl. IsoFit® headband | 620 g | 640 g | 620 g |
| optrel hardHat (according to EN397 standard) | v | ✓ | v |
| ShadeTronic®(fully automatic pro- tection level adjustment, infinitely variable, can be switched off) | ✓ | | ✓ |
| Overhead welding and welding in extreme positions | v | | ✓ |
| Position Locker (safe open and closed helmet position) | ~ | | v |
| Ampere range | up to 500 A Protection levels 4–14* | up to 280 A Protection levels 4-12 | up to 280 A Protection levels 5–12 |
| Brightness level | 3.0 | 2.0 | 2.5 |
| FadeTronic (Twilight mode) | ~ | ✓ | ✓ |
| EN 379 classification | 1/1/1/1 | 1/1/1/2 | 1/1/1/2 |
| optrel IsoFit® headband | inclusive | inclusive | inclusive |
| Power supply | Solar cells, lithium polymer battery, chargeable via micro USB cable, battery service life 300 to 500 charge cycles | | |
| Sensors | Five sensors | | |
| Sensitivity | Infinitely variable adjustment, new with "Super High" sensitivity and tack welding mode | | |
| Dimensional stability | Welding protection mask: up to 220 °C, protection lens: up to 137 °C | | |
| Eye protection | Ultraviolet/infrared protection: Maximum protection across the entire protection level range | | |
| | | All electric welding processes: ling, SMAW) / MIG/MAG (gas metal | and worlding (MAM) (CMAM) |
| Areas of application | high-performance welding / flu | ux-cored wire welding / TIG welding utting / Not suitable for gas and lase | (TIG, GTAW) / plasma welding / |
| | Gri | nding with clearview (180° field of vis | sion) |
| Standards | CE, UKCA, ANSI, EAC, AS/NZS, fulfils CSA Z94.3 Complies with ISO 16321 standards "TIG+" ("low amp Tig" process) | | |
| Guarantee | 2 years, additional 1 year extended warranty (excluding battery) issued when you register the product within the first 6 months at optrel.com/register | | |
| | * with additional SN+1 protection lens ** for connecting an optrel e3000X PAPR syst | em | |

swiss made

KELCOMETOTHE NORLDOF OPTREL

Protecting professionals since 1986

Your optrel dealer:



optrel.com

f

0



optrel AG Industriestrasse 2 9630 Wattwil Switzerland www.optrel.com info@optrel.com optrel inc. PO Box 1454 East Greenwich, RI 02818 USA optrel.us <u>info_us@optrel.com</u> optrel India Private Ltd. 203–204, C Wing, 2nd Floor Saudamini Commercial Complex Right Busari Colony, Near Dutaa Mandir Pune 411038, India www.optrelindia.com connect@optrelindia.com

9412.312.02