

## KRONOS WELDING BLANKET

### Description

Kronos is a fiberglass fabric with a grey, fire-retardant PU-coating on one side with aluminium pigments to increase the antislip properties and resistance to fraying.

### Application

The maximum application temperature is 550 °C, shortly up to 600°C.

### Conditions for use

- CEPRO recommends the use of multiple layers for maximum protection.
- Always use welding blankets at an angle of at least 15 degrees.
- The temperatures shown are only an indication. The suitability of the selected product should always be tested beforehand.
- Regularly check welding blankets for tears and or other damage. Replace damaged blankets where necessary.
- Welding blankets can be used for many purposes and therefore, no guarantee can be given on their use. The end user is responsible for determining whether the welding blanket is suitable for use in a specific situation and whether it offers sufficient protection during the work to be performed.
- CEPRO welding blankets are sewn on the cut edges with best quality Kevlar thread.

### Characteristics

Kronos is recommended for vertical use, for example as a welding and grinding curtain. Kronos is free of asbestos.

### Available dimensions

Kronos welding blanket, 100 x 100 cm	56.50.61
Kronos welding blanket, 200 x 100 cm	56.50.62
Kronos welding blanket, 200 x 200 cm	56.50.65
Kronos welding blanket, 200 x 300 cm	56.50.66
Kronos welding blanket, 300 x 300 cm	56.50.67
Kronos welding blanket, 400 x 300 cm	56.50.68
Kronos welding blanket, 400 x 400 cm	56.50.69
Kronos welding blanket, 400 x 600 cm	56.50.692
Part of a roll, width 100 cm	56.50.06.1000
Full roll 25 m <sup>1</sup> , width 100 cm	56.50.06.1025
Made to size welding blanket	56.50.60

