



WPO 14-15 E marine polishing set

Boat polisher

Polishing set for boat repairs.

Product number: 7 221 48 60 00 0

Details

- + Ideal speed range with infinitely variable speed control for professional surface machining on boats.
- Maximum speed stability at any load over the full setting range thanks to mechanical gear reduction in conjunction with the FEIN highpower motor.
- Special system accessories for the efficient refurbishment of used car paintwork, new car paintwork and highly scratch-resistant paints, and for cleaning, sanding and polishing boat surfaces and gelcoat layers.
- + Convenient speed adjustment.

- + Does not heat up in continuous use.
- + Handle cover for excellent ergonomics.
- + Spindle lock.
- + Right or left-handed operation.
- + Restart protection.
- + Soft start.
- + Carbon brushes with self cut-off function.
- + Can be converted to rotary sander with extractor hood and backing pad.
- Wide range of accessories.
- + Tool also available without accessories (7 221 48).

Price includes

- + 1 anti-vibration handle
- + 1 support plate with hook and loop fastening, Ø 170 mm
- + 1 plastic carrying case

- + 1 Grip hood
- + 1 polishing pad, Ø 195 mm

Product feature

- + Soft start
- + FEIN high-power motor

- + Restart protection
- + Spindle lock

Application

Polishing





Rough sanding Fine sanding Dry sanding

TECHNICAL DATA

Micro-sanding + suitable ++ well suitable Technical data

VIBRATION AND SOUND EMISSION **VALUES**

Input	1,200 W	Sound pressure level LpA Uncertainty of measured value KpA	84 dB 3 dB
Output	750 W		
Speed, no load	500 - 1,500 rpm	Sound power level LWA Uncertainty of measured value KWA	95 dB 3 dB
Polishing disc Ø	230 mm	Sound peak value	100 dB
Mounting thread	M 14	LpCpeak Uncertainty of measured value KpCpeak	3 dB
Cable with plug	4 m	L. ele es	
Weight according to EPTA	2.50 kg	Vibration value 1 α hv 3-way Uncertainty of measured value $K\alpha$	αh,P 2,5 m/s²
		Vibration value 2 αhv 3-	α h,SG 2,5 m/s²

way

Uncertainty of measured value

Application examples









