GBC 2700 Saw

RAPID

Pipe Cold Cutting Recip Saw



	B. Comment		E-Z SAW	E-SAW E
*	Locking tube range	mm	25-323 o/d.	25-323 o/d.
*	Recommended working range	" (o/d.)	1"-20"	1"-20"
**	Torque	kgm	19,0	27,0
***	Max operating temperature	C°	55	55
***	Max noise level	dB	75	75
**	Pneumatic motor power	hp	1,33	-
**	Air consumption	cfm	55-60	-
**	Air working pressure	psi	90	-
*	Air hose connection	inches	3/4"	-
**	Electric motor power	watt	-	1400 (adj.)
**	Alimentation	volt	-	220
**	Frequency	Нz	-	50
***	Idle speed	strokes/min	300	450
*	Unit weight	kg	11,0	9,0
*	Packing dimensions	mm	640x280x130	640x280x130
*	Packing weight	kg	16	14

- Range: 1" to 20".
- **Function:** cutting up to 45° inclination.
- Material: any kind of steel.
- Power: pneumatic or electric.
- Note: The lightweight construction and ease of set up and operation makes it ideal for site work applications. It is capable of cutting most materials including stainless steel.









Cutting blades for carbon steel and stainless steel materials.

- * mechanical data
- ** mathematical data
- *** average data