

# Wire kit

## AVC-OSC



**Combined with an AVC-OSC (Arc Voltage Control-Oscillation) plate enables precise, consistent multi-layer passes for high-quality welds**

### SPECIFICATIONS

- Travelling distance (AVC and OSC) -12,5 mm to + 12,5 mm (+/- 0.49")
- Additional equipment necessary:
  - Plate for each weld head
  - Wire holder Version Pro for OSC applications
- Easy and fast assembly and disassembly

### TECHNICAL DATA

weld head	range	range with screwing clamps	weight without hose package*
OWH-76 AVC-OSC	10 - 80 mm 0.39" - 3.15"	10 - 40 mm 0.39" - 1.57"	4,6 kg 10.14 lbs
OWH-114 AVC-OSC	20 - 115 mm 0.79" - 4.53"	20 - 50 mm 0.79" - 1.97"	5,75 kg 12,68 lbs
OWH-168 AVC-OSC	25 - 170 mm 0.98" - 6.69"	25 - 80 mm 0.98" - 3.15"	9 kg 19.84 lbs
OWH-273 AVC-OSC	101 - 273 mm 3.98" - 10.75"	101 - 170 mm 3.98" - 6.69"	16,9 kg 37.26 lbs

\*hose package depends if the head is used with or without wire feeder and if the torch is gas- or water-cooled.