



FORM MT200

CREATE, REPAIR & CUSTOMIZE

- High-performance dual voltage inverter for 115V and 220V
- Two dynamic welding modes: GTAW (TIG) and SMAW (Stick)
- Easy-to-use interface allows for quick setting adjustments
- Compact, portable design for use in multiple applications

QUALITY VERSATILITY

PERFORMANCE

COMPLETE SYSTEM INCLUDES:

MT200-AC/DC Welding Machine CK17 Flex-Head Gas-Cooled TIG Torch Super-Flex[™] Cables with Dinse Connector AK-3 Accessory/Consumable Kit Ground Clamp Single-Flow Regulator Power Adapter

"As a welder of critical aircraft hardware, this machine is extremely easy to use and runs as smooth as our more expensive machines at work." – R. Harper, AIRCRAFT WELDER, 38 YEARS EXPERIENCE

MT200-AC/DC



www.CKWORLDWIDE.com





POWER & PERFORMANCE IN A COMPACT DESIGN

The MT200-AC/DC is the answer to both creativity and production driven TIG welding. This innovative TIG welding machine provides the ability to quickly and efficiently adapt to dynamic welding situations, while maintaining the same quality of experience you have come to expect from CK Worldwide.

Its compact portable design allows you to easily tackle any project from fabrication and education to aerospace and nuclear applications. Whether you TIG weld for enjoyment or as a career you will find that the MT200 can help you accomplish your toughest welding challenges.

With background testing performed by production welders and the best TIG welding professionals in the industry the MT200 delivers precision welding in a conveniently packaged system.

COMPLETE WELDING SYSTEM INCLUDES:

- MT200-AC/DC
- CK17 Flex-Head Torch with 12.5' (3.8m) Super-Flex[™] Cables CK17-12-RSF FX
- Dinse Connector SL2-35MT
- AK-3 Accessories/Consumables Kit AK-3
- Foot Pedal Amperage Control
- Ground Clamp with 12.5' (3.8m) Cable
- Single Flow Regulator
- 6' (1.8 m) Gas Hose ARH-6
- 220V to 115V Power Adapter

ACCESSORIES / CONSUMABLES AK-3

CKI7 FLEX-HEAD TORCH CK-17-12-RSF FX 150 amp ACHE or DCSP @ 10



150 amp ACHF or DCSP @ 100% Gas-Cooled Length: 8-3/4" (22.2cm) Weight: 5 oz. (141gm)






FOOT PEDAL

AMPERAGE CONTROL

DINSE CONNECTOR SL2-35MT







Advanced technology with an easy-to-use interface, perfect for all welders, from the novice to the master craftsman



SPECIFICATIONS

Input Voltage	115VAC ±15%, 50/60Hz
	220VAC ±15%, 50/60Hz,
	single phase
Input Current (I max)	115V: 21 Amps
	220V: 34 Amps
Output Current Range GTAW	115V: 5 – 140 Amps
	220V: 5 – 200 Amps
Output Current Range SMAW	115V: 10 – 110 Amps
	220V: 10 – 160 Amps
Rated Output GTAW	115V: 140A @ 15.6V,
	40% duty cycle
	220V: 200A @ 18.0V,
	25% duty cycle
Rated Output SMAW	115V: 110A @ 24.4V, 25% duty cycle
	220V: 160A @ 26.4V, 30% duty cycle
Max. Open Circuit Volts	74 volts
Gas Pre-flow	0.5 seconds
Gas Post-flow	0.5 – 20 seconds
AC Frequency	20 – 250 Hz
Pulse Frequency	1 – 200 Hz
Pulse Width	50%
Base Current	10 – 100%
Arc Start	High Frequency
Dimensions	Height: 15 in. (381mm)
	Width: 8.5 in. (217 mm)
	Length: 20 in. (502 mm)
Weight	32 lb. (14.5 kg)


www.CKWORLDWIDE.com





Use the MT200-AC/DC to weld:

- Aluminum
- Titanium
- Magnesium
- Stainless Steel
- Low Alloy Steel
- Deoxidized Copper
- And much more!



USTOMIZATION



FORM MT200







CK WORLDWIDE. INC.

Phone: 1.800.426.0877 Fax: 1.800.327.5038 P.O. Box 1636, Auburn, Washington 98071 USA

> Super-Flex[™] is a trademark of CK Worldwide Inc. © 2015/2016 CK Worldwide, Inc. All rights reserved. #109077 5/2016



CONNECT WITH US ON: 🔊 💟 🖪 👪 in 💱

www.CKWORLDWIDE.com